

Barjo Bespoke Dog Guard Seat Lock Fitting Instructions

Before starting the fitting please read the instructions fully. Barjo recommends the fitter has an assistant to help fit the dog guard.

Barjo Cages & Dog guards Limited cannot accept responsibility for any damage incurred while fitting or from use of the dog guard. If the person fitting the dog guard has any doubt about the fitting, please contact a member of the Barjo team on Tel: 01189 890 240 from Monday to Friday (09.00 – 17.00) or via email info@barjo.co.uk

Before starting, remove any boot liners or matting from your boot. The dog guard will not fit properly with these sat underneath. You will be able to adjust the liners/matting to shape around the dog guard after it is fitted.



Before inserting the dog guard, fold down all rear seats in the vehicle. Place the dog guard into the rear of the vehicle through the boot opening. The Barjo logo will be facing the rear of the vehicle. You may need to enter through the rear passenger door to adjust the dog guard into place. The dog guard must go past the vehicles seat lock mountings and be in an upright position.

Care must be taken not to damage the vehicle trim and fittings during this operation. When the dog guard is in a central position behind the rear seats return the seats to their fully upright position. This will clamp the seat locks in place. Be careful not to trap the seatbelts.

Congratulations your Barjo dog guard is now ready for use.



To clean your dog guard, use a weak solution of waxed car shampoo then dry fully. With all moving parts treat with WD40 or a light machine oil.